



## Prodigy™

*Workforce management, affordably*

Prodigy™ — The ideal blend of performance, function, style, and affordability designed for essential workforce management functionality.

Prodigy is for those who demand a rich suite of features at an affordable price: Web services, customizable function keys, optional biometrics, and more!

Biometric options protect employees' personal information and eliminate costly buddy-punching.

### Prodigy™ features include:

- Internet appliance
- On-board diagnostics
- Biometric options for increased personal security
- Programmable function keys
- Ergonomic design with angled card slot
- Works in WAN and LAN environments
- Optional GSM/GPRS modem
- Optional power-over-Ethernet module



Shown with optional biometric and card readers



# Prodigy Terminal Specifications

<b>DISPLAY</b>	128 x 32 pixel LCD
<b>CLOCK</b>	Battery-backed real-time clock, 12- or 24-hour format (quartz precision)
<b>KEYPAD</b>	16-key tactile 4x4 matrix Numeric keypad, 0-9 4 software-defined function keys (e.g. in/out and two other functions) Customizable overlay allows for unique graphic options
<b>MEMORY</b>	Linux: 32 MB RAM and 32 MB flash  Optional: Java™/Python 128 MB RAM and 128 MB flash
<b>PROGRAMMING</b>	Java™ and Python options Web services capable ATS Universal Command Set or third-party custom application packages
<b>PLATFORM</b>	Linux®
<b>DIAGNOSTICS</b>	On-board diagnostics capability
<b>INTERFACE</b>	Standard 802.3 10/100 BASE-T Ethernet with DHCP Optional EIA standard RS232 Optional internal modem (FCC Part 68 certified) Optional GSM/GPRS modem Optional 802.11 B/G Wi-Fi module USB port for mass storage device
<b>ENCLOSURE</b>	High impact polymer
<b>POWER</b>	12 VDC (nominal) 1.25A, 15W maximum Optional uninterruptible power supply with charger Optional IEEE 802.3af-compliant power over Ethernet
<b>ENVIRONMENT</b>	Operation Temperature: 0° to 50°C (32° to +122°F) Storage Temperature: -20° to 80°C (-4° to +176°F)
<b>PHYSICAL</b>	18.4 cm x 21.3 cm x 9.65 cm (7.25" x 8.40" x 3.80")
<b>CERTIFICATIONS</b>	CE Mark, FCC Part 15 Class A
<b>ACCESSORIES</b>	<ul style="list-style-type: none"><li>• Biometric readers – 1:1 and 1:n – fingerscan</li><li>• Integrated visible or infrared barcode readers</li><li>• Integrated magnetic stripe readers</li><li>• Smartcard readers – contactless (Mifare™, iClass®)</li><li>• Integrated proximity readers</li><li>• Solid-state or dry-contact relay modules</li><li>• Serial interface for printer</li></ul>

## ACCU-TIME SYSTEMS INC. THE AMERICAS – APAC

Corporate Headquarters  
420 Somers Road  
Ellington, CT 06029  
TEL: +1 (860) 870-5000  
FAX: +1 (860) 872-1511  
Toll Free: 1 (800) 355-4648  
sales@accu-time.com  
www.accu-time.com

## CANADA

Toll Free: 1 (800) 358-9132  
sales@accu-time.com

## EMEA

United Kingdom  
TEL: + 44 (0) 1202 606068  
sales@accu-time.com

## All Other Locations

TEL: +44 (0) 2920 885599  
sales@accu-time.com



AN **AMANO** GROUP COMPANY

To learn more about ATS, visit [www.accu-time.com](http://www.accu-time.com) or call 1(800) 355-4648  
As part of Accu-Time's continuous improvement process, we reserve the right to change product specifications without notice.060915